

The perfect complement
to protect your head when
used under the toughest
conditions.



BUMP CAP AND SPECIAL PROTECTIVE HELMET

- +++ 2 variants depending on requirements
- +++ Improved safety
- +++ Compatible with all optrel helmets

PROTECTION AGAINST HEAD IMPACTS AND ABRASIONS.

OPTREL BUMPCAP

Integrated SP30
Foam padding for
additional protection

Art. no. 5002.840
optrel bumpcap
bump cap

click & turn closures
for quick mounting



EN PPE TYPE 1 INDUSTRIAL BUMPCAP

Complies with (EU) ordinance 2016/425 and the general requirements of the EN 812:2012 standard

The bump cap can easily be secured onto the headband.

Suitable for all optrel helmets with comfort headband (optrel standard).

Technical data (excerpt)

Head size	52 cm to 63 cm
Application	All welding and grinding work where there is a risk of head impact or abrasion Confined spaces (e.g. in container construction, robot programming) Additional splash guard
Total weight	130 g
Standards	DIN EN 812
Certifications	CE, 89/686/EEC Directive

TECHNOLOGY AND VISION

The additional impact protection enables the metal processor to move more quickly even in confined environments without the risk of abrasions or injuries.

If the bump cap is allowed as an alternative to an industrial helmet, fatigue is reduced thanks to the significantly lower weight.

PROTECTION AGAINST STRONGER IMPACTS AND FALLING OBJECTS.

OPTREL KONG INDUSTRIAL SAFETY HELMET

Slots for optimum ventilation

Modern helmet design in 5 different colours

Removable and washable padding

Art. no. 5011.130
optrel Kong
Industrial safety helmet
Black



Art. no. 5011.180
Industrial helmet upgrade kit (spring adapter)



Colour	Art. no.
Black	5011.130
White	5011.131
Red	5011.132
Orange	5011.133
Yellow	5011.134
White (US version)	5011.141

EN 397 INDUSTRIAL SAFETY HELMET

optrel Kong industrial safety helmets meet the DIN EN 397 standard; they protect the wearer against falling objects.

The industrial safety helmet is attached to the optrel helmet with a spring adapter.

Fits all optrel helmets WITHOUT a fresh air adapter, and the fresh air version of the optrel clearmaxx und optrel panoramaxx.

Technical data (excerpt)

Head size	52 cm to 64 cm
Application	All welding and grinding work with increased protection requirements; Plant engineering, indoor/outdoor construction sites, industrial helmet obligation
Total weight	388 g
Standards	DIN EN 397

HEAD PROTECTION AS A SUPPLEMENT TO EYE AND RESPIRATORY PROTECTION

Occupational safety equipment against mechanical impact to the head protects the user from potential consequences such as brain injuries and skull fractures. Depending on the working environment and hazardous situation, the welding or grinding helmet must be equipped with additional head protection.

In addition to the conventional industrial safety helmets, optrel also offers a bump cap for protection against lighter impact and a special industrial safety helmet for more powerful impact.

Your optrel retailer:



optrel AG
industriestrasse 2
CH-9630 wattwil
Switzerland
www.optrel.com
info@optrel.com

optrel.com

